**IN THE CLAIMS:**

**Kindly replace the claims of record with the following full set of claims:**

1.      (Previously amended)  A method of motion-compensated predictive image
encoding, comprising the steps of:

estimating (ME) first motion vectors (MVc, MV*l*, MVr, MVa, MVb) associated
with a set of first objects of a fixed size, said motion vectors MV*l*, MVr, MVa, MVb
being associated with first objects adjacent to a first object associated with the MVc
motion vector;

filtering (MVPF) every occurrence of said first motion vectors (MVc, MV*l*, MVr,
MVa, MVb) to obtain second motion vectors (MV1, MV2, MV3, MV4) for second
objects having a fixed size smaller than said first objects fixed size;

generating (3) prediction errors in dependence on said second motion vectors
(MV1, MV2, MV3, MV4) only;

combining (VLC) said first motion vectors (MVc, MV*l*, MVr, MVa, MVb) and
said prediction errors; and

providing an indication said prediction errors are in dependence upon said second
motion vectors.

2. (Previously presented)      A method as claimed in claim 1, wherein said first objects
are macro-blocks having a fixed size of (16*16) pixels, said second objects are blocks
having a fixed size of (8*8)  pixels and said filtering step (MVPF) comprises the steps of:

providing x and y motion vectors components of a given macro-block (MVc) and

of macro-block (MV*l*, MVr, MVa, MVb) adjacent to said given macro-block (Mvc); and

supplying for each block (MV1) of a number of blocks (MV1-MV4)

corresponding to said given macro-block (MVc), x and y motion vector components

respectively selected from said x and y motion vector components of said given macro-

block (MVc) and from the x and y motion vector components of two blocks (MV*l*, MVa)

adjacent to said block (MV1).

3 (Previously amended)    A device for motion-compensated predictive image

encoding comprising:

means for estimating (ME) first motion vectors (MVc, MV*l*, MVr, MVa, MVb)

associated with a set of first objects of a fixed size, said motion vectors MV*l*, MVr, MVa,

MVb being associated with first objects adjacent to a first object associated with the MVc

motion vector;

means for filtering (MVPF) every occurrence of said first motion vectors (MVc,

MV1, MVr, MVa, MVb) to obtain second motion vectors (MV1, MV2, MV3, MV4) for

second objects having a fixed size smaller than said first objects fixed size;

means for generating (3) prediction errors in dependence on said second motion

vectors (MV1, MV2, MV3, MV4) only; and

means for combining (VLC) said first motion vectors (MVc, MV*l*, MVr, MVa,

MVb) and said prediction errors; and

means for providing an indication said prediction errors are in dependence upon

said second motion vectors.

4. (Previously amended)     A method of motion-compensated predictive decoding,

comprising the steps of:

responsive to an indication of processing prediction errors that are in dependence

upon a second motion vectors,

generating (VLC$^{-1}$) first motion vectors (MVc, MV$l$, MVr, MVa, MVb)

and prediction errors from an input bit-stream, said first motion vectors (MVc,

MV$l$, MVr, MVa, MVb) relating to first objects of a fixed size, and said motion

vectors MV$l$, MVr, MVa, MVb being associated with first objects adjacent to a

first object associated with the MVc motion vector, and said prediction errors

related to second objects having a fixed size smaller than said first objects fixed

size only;

filtering (MVPF) every occurrence of said first motion vectors (MVc, MV$l$, MVr,

MVa, MVb) to obtain second motion vectors (MV1, MV2, MV3, MV4) for said second

objects; and

generating (15, MC) an output signal in dependence on said prediction errors and

said second motion vectors (MV1, MV2, MV3, MV4).


5. (Previously presented)     A method as claimed in claim 4, wherein said first objects

are macro-blocks having a fixed size of (16*16) pixels, said second objects are blocks

having a fixed size of (8*8) pixels, and said filtering step (MVPF) comprises the steps

of:

providing x and y motion vectors components of a given macro-block (MVc) and

of macro-block (MV$l$, MVr, MVa, MVb) adjacent to said given macro-block (Mvc); and

supplying for each block (MV1) of a number of blocks (MV1-MV4) corresponding to

said given macro-block (MVc), x and y motion vector components respectively selected

from said x and y motion vector components of said given macro-block (MVc) and from

the x and y motion vector components of two blocks (MV1, MVa) adjacent to said block

(MV1).

6. (Previously amended) A device for motion-compensated predictive decoding,

comprising:

means for determining an indication of processing prediction errors that are in

dependence upon second motion vectors,

means for generating (VLC⁻¹) first motion vectors (MVc, MV*l*, MVr, MVa, MVb)

and prediction errors from an input bit-stream, said first motion vectors (MVc, MV*l*,

MVr, MVa, MVb) relating to first objects of a fixed size (16*16), said motion vectors

MV*l*, MVr, MVa, MVb being associated with first objects adjacent to a first object

associated with the MVc motion vector, and said prediction errors related to second

objects (8*8) only;

means for filtering (MVPF) every occurrence of said first motion vectors (MVc,

MV*l*, MVr, MVa, MVb) to obtain second motion vectors (MV1, MV2, MV3, MV4) for

said second objects having a fixed size smaller than said first objects fixed size; and

means for generating (15, MC) an output signal in dependence on said prediction

errors and said second motion vectors (MV1, MV2, MV3, MV4).

7. (Previously presented)    A multi-media apparatus, comprising:

means (T) for receiving a motion-compensated predictively encoded image

signal; and

a motion-compensated predictive decoding device as claimed in claim 6 for

generating a decoded image signal.

8. (Previously presented)    An image signal display apparatus comprising:

means (T) for receiving a motion-compensated predictively encoded image

signal;

a motion-compensated predictive decoding device as claimed in claim 6 for

generating a decoded image signal; and

means (D) for displaying said decoded image signal.

9. (Previously amended)    A method for generating a motion-compensated

predictively encoded image signal, comprising:

estimating first motion vectors (MVc, MV$l$, MVr, MVa, MVb) related to first

objects of size (16*16) pixels; obtaining second motion vectors (MV$l$, MV2, MV3, MV4)

for second objects of size (8*8) pixels from said first motion vectors (MVc, MV$l$, MVr,

MVa, MVb), generating prediction errors relating to every occurrence of second objects,

wherein said prediction errors depend on said second motion vectors (MV1, MV2, MV3,

MV4) only and providing an indication said prediction errors are in dependence upon

said second motion vectors.